# Specification



Model			SP05A (2WD)	SP05A (3WD)
Dimensions	Total length		84.65 in (with blade 90.55 in) I 215 cm (with blade 230 cm)	
	Total width		74.80 in <b>I</b> 190 cm	
	Total height		47.24 in I 120 cm	
Weight (with empty fuel tank)			974.43 lb l 442 kg	1033.95 lbl 469 kg
Minimum turning radius			133.46 in   339 cm	
Engine -		Model	Vanguard 356447	
		Туре	Air-cooled 4-cycle gasoline engine	
		Total displacement	34.78 cu.in.   570 cm <sup>3</sup> (0.57 L)	
		Maximum output	13.2 kW (18.0 PS)/3,600 rpm	
Fuel tank capacity			Gasoline 3.96 U.S.gal. I Gasoline 15.0 dm³ (15.0 L)	
Operating width (Mowing width)			109.06 in   277 cm	
Operating width (Mowing width)		Rake	74.80 in I 190 cm	
		Blade (option)	31.50 in (Weight: 55.11 lb) I 80 cm (Weight: 25 kg)	
		Cultivator (option)	45.67 in (Weight: (41.89 lb)   116 cm (Weight: 19 kg)	
		Finishing brush (option)	76.77 in (Weight: (23.37 lb) I 195 cm (Weight: 10.6 kg)	
Drive			HST, 2WD/3WD selectable	
Speed (HST)		Forward	0 - 9.94 mph   0 - 16.0 km/h	0 - 7.96 mph   0 - 12.8 km/h
		Reverse	0 - 3.73 mph   0 - 6.0 km/h	0 - 3.73 mph   0 - 6.0 km/h
Maximum inclination for operation		15 degrees		
Tire size		Front wheel	PD21 x 11.00 - 10	
		Rear wheel	25 x 13.00 - 9	
The factory default maximur	n engine rpm is	s 3,100 rpm.		[GB/US]



\*The model shown is equipped with optional features.

Your distributor or dealer

#### Safety notes

Read the Owner's Operating Manual and other training material carefully.

Be familiar with the controls, safety signs and the proper use of equipment before operation.

#### Assurance inspection

Regular inspection of the machine ensures long-lasting superior performance and safety.
There are parts of machine prone to wear and deterioration from long periods of use.
Please consult with local dealer or distributor for proper inspection and maintenance schedule.

# 株式会社 共栄社

### KYOEISHA CO., LTD.


1-26, Miyuki-cho, Toyokawa-city, Aichi-pref, 442-8530 Japan TEL+81 533-84-1390 FAX+81 533-84-1220

www.baroness.co.jp

Quality on Demand









Bunker Rake

# SP05A



This Bunker Rake is designed to adapt to all kinds of bunker conditions with power steering, switchable 2WD/3WD, low center of gravity and free-floating adjustable rake and finishing brush.



#### **SP05A Features**

- ·Special rake design enables flexible rake movement.
- ·High-speed transport, can travel around course quickly.
- Power steering allows for shorter turning radius, also reducing operator fatigue.
- ·Low-vibration and low-noise.
- •Front and rear covers open fully, for easy accessibity and maintenance.
- •The foot brake increases safety.







## **Options**



The Brush option beautifully finishes the bunker surface.



The front blade option smoothes and evens the bunker.



The cultivator option breaks up and softens coarse sand.



The headlight options are mounted on the front and rear. These lights are useful for early morning operation.



The cargo box option allows operator to carry cooler, walkie-talkie and other necessary tools.

