

Ideal verticutting work on the fairways

A verti-cutter unit helps thin out the grass, promote rooting of the new grass, and revitalize the turf.

VM62/VM66/VM60 Features:

- Baroness New Verti Cutter Option
- 3 or 5 gang mower options
- Maximum working depth is 0.24 in (6 mm)
- A scraper is attached to the rear roller to prevent sand from getting on the roller.







Specifications

Model		VM62	VM66	VM60
Specifications		22inch with Rear Scraper	26inch with Rear Scraper	30inch with Rear Scraper
Dimensions	Length	14.3 in 363.6 mm	14.3 in 363.6 mm	14.3 in 363.6 mm
	Width	29.3 in 744.3 mm	33.3 in 846.8 mm	37.6 in 954.8 mm
	Height	8.6 in 219.5 mm	8.6 in 219.5 mm	8.6 in 219.5 mm
Weight		79.4 lb 36 kg	88.2 lb 40 kg	97 lb 44 kg
Cutting work max depth		0.24 in 6 mm	0.24 in 6 mm	0.24 in 6 mm
Cutting work max height		0.79 in 20 mm	0.79 in 20 mm	0.79 in 20 mm
Blade Number		12	14	16
Optional for		LM2700,LM551	LM2700,LM281	LM3210

^{*}Reguired each original connecting parts.



Safety notes

 Read the Owner's Operating Manual and other training material carefully. Be familiar with the controls, safety signs and the proper use of equipment before operation.



Assurance inspection

●Regular inspection of the machine ensures long-lasting superior performance and safety. • There are parts of machine prone to wear and deterioration from long periods of use. Please consult with local dealer or distributor for proper inspection and maintenance schedule



株式会社 共栄社

KYOEISHA CO., LTD.

1-26, Miyuki-cho, Toyokawa-city, Aichi-pref, 442-8530 Japan TEL+81 533-84-1390 FAX+81 533-84-1220

www.baroness.co.jp



Your distributor or dealer

