Option

Groomer

Dethatcher

Dethatching brush

Rear roller brush









Front scraper (with Groomer)



Front scraper (without Groomer)



Reel cutter (7, 9, 11 blades)





Specifications

Model			LM311	
Dimensions	Total length		250 cm	98.42 in
	Total width		191 cm	75.20 in
	Total height	Steering wheel	140 cm	55.12 in
		ROPS	195 cm	76.77 in
Weight	Machine:2WD (empty fuel tank)	without ROPS, Grass box, Groomer	682 kg	1503.6 lb
	Machine:3WD (empty fuel tank)	without ROPS, Grass box, Groomer	709 kg	1563.1 lb
	Grass boxes (for one machine)		15 kg	33.07 lb
	Groomers (for one machine)		10 kg	22.05 lb
	ROPS + Seatbelt		28 kg	61.73 lb
Minimum turning radius			161 cm	63.39 in
Engine	Model		Kubota D722-E4B	
	Туре		Vertical water-cooled 4-cycle diesel engine	
	Total displacement		719 cm³ (0.719 L)	43.87 cu.in.
	Rated output		12.4 kW (16.9 PS)/3,000 rpm)	
Fuel tank capacity			Diesel 19.2 dm ³ (19.2 L)	Diesel 5.07 U.S.gals
Operating width (Mowing width)			157 cm	61.81 in
Operating height (Mowing height)			1.5 - 18.0 mm(for tees : 6.0 - 28.0 mm)	0.059 - 0.709 in(for tees : 0.236 - 1.102 in)
Number of blades			7, 9, 11	
Drive	Traveling		HST 2WD [3WD (2WD/3WD selectable)]	
	Mowing		Hydraulic	
Speed (HST)	Forward		0 – 15.0 km/h	0 - 9.32 mph
	Reverse		0 - 6.0 km/h [2WD selection of 3WD model : 0 - 9.0 km/h]	0 - 3.73 mph [2WD selection of 3WD model : 0 - 5.59 mph]
Efficiency			7,536 m²/h (6.0 km/h x mowing width x 0.8)	1.8 acres/hour (3.73 mph x mowing width x 0.8)
Maximum inclination for operation			15 degrees	
Tire size	Front wheel		Smooth 19 x 10.50-8 4P	
	Rear wheel		Smooth 19 x 10.50-8 4P	







In pursuit of creating amazing greens

Baroness reel cutter

Because of Baroness's unique manufacturing method, our reel cutter doesn't easily wear out and is long-lasting. It can maintain its cutting quality for a long time while mowing. With our manufacturing experience and expertise of over 50 years, many greenskeepers have come to trust the Baroness reel cutter for its quality.



"B-ACT is a system for adjusting the angle of the bedknife. Through B-ACT, the turf condition can be modified to the required ball speed without changing the cutting height. B-ACT helps create the turf condition that greenskeepers worldwide aim for."








Selectable reel rotation speed




The reel rotation speed can easily be adjusted for optimal cutting based on the condition of the turf.

Flexible mower units



With improved supporting arms containing multiple fulcrums, the mower units can accurately follow the contour of any surface.

All hydraulic system



The all hydraulic system drives the reels, providing stable reel rotation and powerful cutting performance. It also simplifies maintenance and contributes to cost saving.

Designed for comfortable and efficient



Control panelThe centralized control panel improves operational efficiency.



Vibration reduction design
The vibration reduction
design reduces the operator's
fatigue and helps prolong his
concentration.



Exhaust system Exhaust noise is reduced.



Slidable seat
The newly designed seat
provides comfort and safety.

operation



Tilt steering
The adjustable tilt steering allows the operator to have a comfortable working posture.



Covers open fully
All the covers can be opened
and closed without tools. As a
result, daily inspection is easy.



Wider tires
Wider tires are used to distribute
the machine's weight widely so
that tire marks after mowing are
reduced to the minimum.



USB portsIt is equipped with two USB ports for charging devices like mobile phones.